

TT - 75

75 LITRES

ELECTRICAL CHARACTERISTICS

- Power Supply: 400V+3F+TF / 14A
- Heating element: 3 x 450W

ULTRASONIC CHARACTERISTICS

- Ultrasonic power: 800Wp (1600Wp-p)
- 1 ultrasonic generator with an output power of 800Wp (1600Wp-p)
- Working frequency: 40 KHz sweep system \pm 2%
- 16 PZT (lead zirconate titanate) piezo-electric transducers with aluminium alloy body.

CONTROL PANEL

- Main breaker
- DEGAS system to degas water
- Ultrasounds timer
- Temperature selector
- Power level selector: 50% - 100%

FINISH AND ACCESSORIES

- Tank made of 2 mm thick stainless steel AISI 316
- External panel in 1 mm thick fingerprint resistant steel
- 20 mm thick thermo-acoustic insulation
- Temperature control via PT100
- Side handles integrated on the external panel
- Stainless steel basket with anchorage system for loading, unloading and draining the parts
- 1" drain ball valve
- Height-adjustable silentblock legs
- Insulated tank cover of Stainless steel

TECHNICAL DATA

- Capacity: 75 litres
- Internal dimensions: 700 x 350 x 400 mm
- Useful dimensions: 650 x 300 x 290 mm
- External dimensions: 1075 x 575 x 900 mm
- Weight: 71 kg



WARRANTY AND PRODUCT QUALITY: All equipments supplied by TierraTech®. are supplied with an instruction manual in English according to the European legislation on CE marking. The equipments comply the directives on electromagnetic compatibility and electrical safety: Directive 2004/108/EC and Directive 2006/95/EC. The equipments have 2 years warranty against manufacturing defects.

Tierra Tech S.L.

Pque. Emp. Morero, nave 27. Guarnizo - Cantabria (SPAIN)

Tel (+34) 942 26 95 43 • Fax (+34) 942 26 95 44 • tierratech@tierratech.com • www.tierratech.com