

MOT - 8000

8600 LITRES

ELECTRICAL CHARACTERISTICS

- Power Supply: 400V
- Heating element: 60000W

ULTRASONIC CHARACTERISTICS

- Ultrasonic power: 34000Wp (68000Wp-p)
- 10 ultrasonic generators with an output power of 34000Wp (68000Wp-p)
- 20 submersibles emitters with a power of 1700Wp (3400Wp-p) made of 2.5 mm thick stainless steel AISI 316L. The emitter contains 34 PZT (lead zirconate titanate) piezo-electric transducers with aluminium alloy body.
- Working frequency: 40 KHz sweep system \pm 2%

CONTROL PANEL

- 7" capacitive touch screen, functional and intuitive, providing access to ultrasonic time settings, temperature control, and peripheral or optional systems.
- Weekly programming available

FINISH AND ACCESORIES

- Tank made of 3 mm thick stainless steel AISI 304L
- External panel in 1 mm thick fingerprint resistant steel
- 20 mm thick thermo-acoustic insulation
- 2" drain ball valve and 1" filling valve
- Height-adjustable silentblock legs
- 2 automatic insulated tank covers of stainless steel operated by pneumatic cylinders
- Air blow gun for drying the parts
- Integrated waterflow system. Sweeps the waste floating on the surface, keeping the cleaning equipment in perfect condition
- (Optional): Filtration system (stainless steel filter with polypropylene / polyester bag) for waste and mud

TECHNICAL DATA

- Capacity: 8600 litres
- Internal dimensions: 3000 x 2000 x 1495 mm
- Useful dimensions: 2900 x 1900 x 1180mm
- External dimensions: 4820 x 2485 x 1840mm
- Electrical cabinet dimensions: 2200 x 600 x 2000 mm
- Weight: 3500 kg

