

TT - 24G XL GRAPHIC INDUSTRY

18 LITRES

ELECTRICAL CHARACTERISTICS

- Power Supply: 240V
- Heating element: 2x450W

ULTRASONIC CHARACTERISTICS

- Ultrasonic power: 600W (1200Wp-p)
- 1 ultrasonic generator with an output power of 600W (1200Wp-p)
- Working frequency: 40 KHz sweep system \pm 2%
- 12 high-performance IBL piezo-electric transducers in titanium steel

CONTROL PANEL

- Main breaker
- DEGAS system to degas water
- Ultrasounds timer
- Temperature selector
- Power level selector: 50% - 100%

FINISH AND ACCESORIES

- Tank made of 2 mm in thick stainless steel AISI 316L
- External panel in 1 mm in thick fingerprint resistant steel
- 20 mm in thick thermo-acoustic insulation
- Rolling System: Support that allows to rotate the roller in a continuous way with 7.2W AC synchronous motor
- 1" drain ball valve
- Height-adjustable silentblock legs
- Tank cover in stainless steel with pneumatic shock absorber
- Air blow gun for drying the parts

TECHNICAL DATA

- Capacity: 18 litres
- Internal dimensions: 700 x 200 x 190 mm
- External dimensions: 1095 x 400 x 915mm
- Weight: 34 kg
- Maximum diameter of the roller in the area to be cleaned: \varnothing 120mm
- Minimum diameter of the roller in the area to be cleaned: \varnothing 60mm
- Minimum length of the area to be cleaned from the roller: 100mm
- Maximum length of the area to be cleaned from the roller: 500mm
- Maximum distance between roller supports: 567mm



WARRANTY AND PRODUCT QUALITY: All equipments supplied by TierraTech®, are supplied with an instruction manual in English according to the European legislation on CE marking. The equipments comply the directives on electromagnetic compatibility and electrical safety: Directive 2004/108/EC and Directive 2006/95/EC. The equipments have 2 years warranty against manufacturing defects.

Tierra Tech S.L.

Pque. Emp. Morero, nave 27. Guarnizo - Cantabria (SPAIN)

Tel (+34) 942 26 95 43 • Fax (+34) 942 26 95 44 • tierratech@tierratech.com • www.tierratech.com