

TT - 4000N

1057 GALLONS

ELECTRICAL CHARACTERISTICS

- Power Supply: 400V
- Heating element: 2x15000W

ULTRASONIC CHARACTERISTICS

- Ultrasonic power: 24000Wp (48000Wp-p)
- ultrasonic generators with an output power of 24000Wp (48000Wp-p)
- 12 submersibles emitters with a power of 2000Wp (4000Wp-p) made of 2.5 mm thick stainless steel AISI 316 steel. The emitter contains 34

high-performance IBL piezo-electric transducers in titanium steel

- Working frequency: 40 KHz sweep system \pm 2%

CONTROL PANEL

- 4.3" touch screen. Functional and intuitive access to ultrasound time setting, temperature and peripheric or optional systems. Programmable weekly calendar
- 6 outputs and 8 inputs temperature module PLC

FINISH AND ACCESORIES

- Tank made of 0.12" in thick stainless steel AISI 304
- External panel in 0.04" in thick fingerprint resistant steel
- 0.79" in thick thermo-acoustic insulation
- Reinforced pneumatic platform for loading and unloading up to 4409 lb
- 2" drain ball valve and 1" filling valve
- Height-adjustable silentblock legs
- Automatic insulated tank cover in stainless steel operated by a pneumatic cylinder
- Air blow gun for drying the parts
- Integrated waterflow system. Sweeps the waste floating on the surface, keeping the cleaning equipment in perfect condition
- (Optional): Filtration system (stainles steel filter with polypropylene / polyester bag) for waste and mud

TECHNICAL DATA

- Capacity: 1057 gallons
- Internal dimensions: 94" x 59" x 50" in
- Useful dimensions: 90" x 54" x 35" in
- Overall dimensions: 164" x 89" x 61" in
- Weight: 6172lb



WARRANTY AND PRODUCT QUALITY: All equipments supplied by TierraTech®. are supplied with an instruction manual in English according to the European legislation on CE marking. The equipments comply the directives on electromagnetic compatibility and electrical safety: Directive 2004/108/EC and Directive 2006/95/EC The equipments have 12 months warranty against manufacturing defects.