

ULTRASONIC 20

FERROUS CLEANER DEGREASER ULTRASOUND MACHINE PARTS

ULTRASONIC 20 is a specially formulated to be used as hot-dip degreasing of ferrous parts in ultrasonic cleaning machines product.

With its balanced formulation of surfactants, sequestering and alkalis, ULTRASONIC 20 has properties particularly suitable for removing encrusted grease, oils and any dirt hard, preventing redeposit on the cleaned parts sediments. His quelating agents prevent the precipitation of calcium and magnesium, the product when used in hard water without altering its cleaning power sales. Its surfactants carefully selected facilitate the penetration of the product into the soil giving a great detergent and degreaser.

ULTRASONIC 20 contains in its formulation surfactants reduce the surface tension of water, giving a great moisturizing power.

DOSAGE AND METHOD OF USE

ULTRASONIC 20 is used diluted in ultrasonic water tank to a ratio of 2-5 %.

TECHNICAL SPECIFICATIONS

COLOR	WHITE
APARENCE	POWDER
ODOR	CHARACTERISTIC
RELATIVE DENSITY	0,76 +/- 0,05 g/cm ³
pH 1%	11,5 +/- 0,5

CONTAINS

From 5 – 15 %	Phosphates
Less than 5 %	Nonionic surfactants
Less than 5 %	Anionic surfactants

This product meets the existing legislation on biodegradability and Technical Sanitary Regulation on Detergents.